


Symbol



Features

- * For high pressure use, corrosion and chemical resistance.
- * Good performance in chemically working environments and outdoor facility.
- * Suitable for semi-conductor industry.
- * Lubricator oil can be replenished without stopping air supply.
- * Oil spray in mist ensures good lubrication for machines.



How to order

US

 SUS316
Stainless steel

LC

Lubricator

06

Port size

| | |
|----|------|
| 06 | 3/4" |
| 08 | 1" |

N

Thread

| | |
|-------|-----|
| Blank | PS |
| N | NPT |

Specifications

| Model | USLC-06 | USLC-08 |
|--|------------------------------|---------|
| Port size | 3/4" | 1" |
| Fluid | Compressed air | |
| Body material | Stainless steel SUS316 | |
| Bowl material | Stainless steel SUS316 | |
| Operating pressure range | 0.5 ~ 30 kgf/cm ² | |
| Lubricator bowl capacity | 200cc | |
| Max. inlet pressure | 60 kgf/cm ² | |
| Max. flow rate l/min (6kgf/cm ²) | 7250 | 7650 |
| Lubricator oil (Recommended) | ISO-VG32 | |
| Ambient temperature | -10°C ~ 70°C | |
| Net weight | 2500g | |

Dimensions

USLC-06, 08

