


## Symbol



Filter

## Features

- \* For high pressure use, corrosion and chemical resistance.
- \* Good performance in chemically working environments and outdoor facility.
- \* Suitable for semi-conductor industry.
- \* Effectively removes water and particle.
- \* Strict quality control.
- \* Light weight, compact size for space saving.



## How to order

**SSF200**

Stainless steel SUS316 Miniature F.R.L

Miniature Filter

**02**

Port size

02 1/4"

**N**

Thread

Blank	PS
N	NPT

**H**

Drain

Blank	Semi-auto drain
H	Manual drain
D	Auto drain

## Specifications

Model	SSF200
Port size	1/4"
Fluid	Compressed air
Body material	Stainless steel SUS316
Bowl material	Stainless steel SUS316
Filter element material	Stainless steel SUS316
Filtration	5μm (Standard) · 40μm (Option)
Operating pressure range	0.5 ~ 20 kgf/cm <sup>2</sup>
Max. inlet pressure	30 kgf/cm <sup>2</sup>
Max. flow rate	1900 l/min
Ambient temperature	-10℃ ~ 60℃
Filter bowl capacity	105cc
Standard drain	Semi-auto drain (Drains below 0.5kgf/cm <sup>2</sup> )
Net weight	1260g
Accessories	Pressure gauge, Mounting bracket, Plug, Screw x 2

## Dimensions

