

Features

- * The data of power and final temperature are valid for the standard voltages 24VDC and 230VAC; the power consumption may be higher at different nominal voltages.
- * Function is warranted at max. ambient temperature, max. voltage change and operating temperature.
- * The data of final temperature is valid for thermoplastic valve bodies and thermoplastic encapsulated coils. The temperature will be approximately 10-20K higher if the bodies are manifold.
- * This will cause a reduction of the magnetic force.
- * For additional information see German standard "Specification for Electronic Devices" DIN VDE 0580 or folder 1.4.0.0.



Order code

Voltage	Order code	Remarks
220VAC	SA21330DTSNT	Standard (18.1VA)
110VAC	SA11330DSSNT	Standard (17.6VA)
24VDC	SD91330DQSNT	Standard (15W)
48VAC	SA41330DXSN	Option (22VA)
24VAC	SA91330DSNNT	Option (17.6VA)
12VDC	SD71330DQNNT	Option (15W)
12VAC	SA71330DXSN	Option (22VA)

※Special voltage on your request

Specifications

Operating	Normally closed
Coil width	30mm
Voltage tolerance	±10%
Duty cycle	100% ED
Ambient temperature	-20°C ~ 50°C
Isolation class of material	F (according to Din VDE0580)
Degree of protection	IP65 (according to EN60529)
Moulding material	Thermoplastic (PA, PPS)
Rated power DC	15W
Rated power AC (60Hz)	16VA
Rated power AC (50Hz)	19VA
Type	DIN 43650A (ISO4400)

Dimensions

